

November 14, 2017

Addendum to Pages 7-35 and 7-37.

**Figure 7.28.** The section properties were developed on a 160 mm web width for all sizes of CPCI girder. The drawings have all changed from 150 mm web width to 160 mm. There are no changes to the section properties.

**Figure 7.29.** The section properties for NU 1800 have been changed in the table of section properties as highlighted below. There are no changes to the drawing.

Beam Designation	$A_g$ mm <sup>2</sup>	$I$ (10 <sup>6</sup> mm <sup>4</sup> )	$y_b$ (mm)	$S_b$ (10 <sup>3</sup> mm <sup>3</sup> )	$S_t$ (10 <sup>3</sup> mm <sup>3</sup> )	$m$ (kg/m)	$w$ (kN/m)
NU 1000	443,509	60,725	454	133,756	111,218	1,087	10.66
NU 1200	475,509	95,702	542	176,572	145,444	1,165	11.43
NU 1400	507,509	140,081	632	221,647	182,397	1,243	12.20
NU 1600	539,509	194,522	724	268,677	222,057	1,322	12.97
NU 1800	571,509	259,679	816	318,234	263,901	1,400	13.74
NU 2000	603,509	336,204	909	369,861	308,161	1,479	14.51
NU 2400	667,509	525,955	1,097	479,448	403,649	1,635	16.04
NU 2800	731,509	768,950	1,287	597,475	508,229	1,792	17.58